



	Formabind 5115	Formabind 5126	Formabind 1281	Protac 1460	Protac 1492	Castac 315 B	Castac 1502	Castac 11700
gramatura etykiet <70 g	●●●	●●	●●	●●	●●	●●●	●●	●●
gramatura etykiet <85 g	●●	●●	●●	●●●	●●●	●●	●●	●●
gramatura etykiet >85 g	●	●●	●●	●●●	●●●	●	●●	●●
pokrywane	●	●●	●●	●●●	●●●	●	●●	●●●
butelki zimne wilgotne	●●	●●	●●●	●●●	●●●	●	●●	●●●
butelki gorące suche	●●	●●	●●	●●	●●	●●	●●	●●
butelki gorące >40 °C	●●	●●	●●	●●	●	●●●	●	●●
wytrzymałość na roszenie	●●	●●	●●	●●●	●●●	●●	●	●●
pasteryzacja			●●●					
odporność na wodę lodową								●●●
łatwość zmywania	●●●	●●●	●●●	●●●	●●●	●●●	●●●	●●●
polecane do	szkło	szkło,etykiety peel-off	szkło, pasteryzacja	szkło	szkło	szkło, gorący rozlew	szkło, bardzo morke butelki	szkło,odporny na wodę lodową
lepkość mPas (25 °C)	ca. 50000	ca. 70000	ca. 60000	ca. 70000	ca. 75000	ca. 50000	ca. 60000	ca. 80000
zalecana temperatura pracy	22-32 °C	24-32 °C	25-35 °C	24-32 °C	26-35 °C	22-32 °C	25-35 °C	25-35 °C

●●● = szczególnie  
zalecany

●● = może być stosowany